T C H I C L \mathbf{D} A T \mathbf{E} A A

" Dry As a Bone "



DECO TIE PATCH

DECO PRODUCTS, INC.

DESCRIPTION

DECO TIE PATCH was designed for the prevention of water intrusion from the form ties that were removed and/or broken off to meet the ICC requirements which states: "any holes and recesses resulting from the removal of form ties shall be sealed with a bituminous material or other approved methods or materials".

USE

New construction: Seals poured concrete wall ties below grade from the potential risk of water intrusion



TOTALLY WATER BASED 0 % VOC





E

- *Tested by SGS U. S. Testing Company
- *Contains anti fungal ingredients
- *Contains rust inhibitors
- *Can be applied to dry or damp walls



Е F S N

- *Can be painted or coated over
- *Requires only one application
- *Non Toxic, Non Flammable
- *Standard color is gray





For More Information Contact: DECO Products, Inc. 1-800-500-DECO (3326)





SPECIFICATION DATA

TEST DATA:

ASTM D 1970-90 Section 7.7 Low Temperature Flexibility

ASTM D 2939 Section 15 Resistance to water

ASTM D 466-42 Resistance to water action.

ASTME 96 Water vapor transmission.

ICBO AC29 Section 4.4.4.3 and 4.4.4.5 Hydrostatic Pressure Test

ASTM C 836-95 Section 5.7 Hydrostatic Crack Bridging Pressure Test

ASTM D 2665-1999 Color Fastness Of Surface Coating

ASTM D 3273-94 Resistance to Mold Growth of Surface Coating

LIMITATIONS:

Do not let product freeze. Store indoors at temperatures above 32 degrees Fahrenheit. The temperature should be 28 degrees Fahrenheit and rising before application.

Do not add water to DECO TIE PATCH. Do not apply DECO TIE PATCH on glazed tile, slate, glazed brick construction, acrylics or painted finishes. DECO TIE PATCH is designed to be used as a waterproofing material to stop moisture penetration caused by cracks or holes in the surface.

KEEP OUT OF REACH OF CHILDREN

INSTALLATION:

NOTE: Always perform a job site test to insure desired results.

Coverage: Approximately 150 to 1,000 ties can be patched depending on the size of the tie. Do not apply over 120 mi thick.

Equipment cleans up easily with soap and water.

WARRANTY: DECO Products warrants this product to be good quality and will replace or refund the purchase price of this product if proved defective within 1 year from date of purchase. It is the responsibility of the buyer to determine that this product meets their needs and to apply it properly. The application of DECO TIE PATCH requires that the installer be skilled in achieving results form applying this product. Satisfactory results depend not only upon quality product, but also upon many factors beyond DECO Products's control. DECO Products makes no warranty or guarantee, expressed or implied, including warranty of fitness or merchantability respecting its products. DECO Products shall have no other liability with respect thereto. Guarantee of this product, DECO TIE PATCH, when used according to directions, is limited to refund of purchase price or replacement of product, if it is proved defective. DECO Products shall not be liable for cost of labor, direct or incidental consequential damages.

MAINTENANCE:

No maintenance required.

TECHNICAL SERVICES:

Technical advice furnished by DECO Products, concerning any use or application of DECO Products is reliable as current technology allows. DECO Products makes no warranty, expressed or implied, of any use of application for which such advise is furnished. "DECO TIE PATCH" is manufactured by DECO Products, Inc.

DECO TIE PATCH

DECO Products, Inc.

7900 E. 40th Ave.

Denver, Colorado 80207 USA

(800) 500-3326