

# TECHNICAL INFORMATION

## DECO 20 CLEAR FINISH

For use on: Concrete, concrete pavers, roof tiles and concrete grout lines

"dry as a bone"



**DECO PRODUCTS, INC.**

### *Product specification*

DECO 20 CLEAR FINISH is a non- hazardous reactive clear silicate designed to protect and preserve poured concrete, concrete pavers, roof tiles, concrete grout lines and other cementitious substrates from the damaging effects of weather and moisture intrusion. DECO 20 CLEAR FINISH is 100% transparent and leaves no film on the surface.



**Environmentally Friendly**



**Totally Water- Based**



**Non- Hazardous**



## B E N E F I T S

- Protects and preserves cementitious material
- Reduces or eliminates mildew growth
- DRIES CLEAR, non- yellowing, no odor
- Dries in 2- 4 hours
- Only one application required
- Interior or exterior use
- Can be painted or coated over
- Unaffected by Ultraviolet rays
- Non- toxic Non- hazardous Non- flammable

### *Use: For approved applicators*

**New & existing construction:** Clean surface and cover ALL surfaces not intended to be sealed with DECO 20 CLEAR FINISH. DO NOT GET ON GLASS OR GLAZED TILE. Apply DECO 20 CLEAR FINISH without dilution to surface to be treated until saturated. Avoid runs, drips and puddling. Over applying DECO 20 can cause a whitening effect creating an undesirable appearance. Because DECO 20 CLEAR FINISH is water- based it cannot be applied more than once.

### *Environmental responsibility*

Since 1991 Deco Products has been manufacturing only non- hazardous and solvent free sealers and coatings for the concrete industry. We take pride in communities and neighborhoods and want to preserve and protect our planet for generations to come.



BUILT GREEN™

Made in the U.S.A.



# S P E C I F I C A T I O N D A T A

## **Preparation:**

Repair all structural deficiencies before applying DECO 20 CLEAR FINISH.

Cover all areas or surfaces not to be sealed, such as doors, windows and floors, prior to applying. Seal or repair all cracks or deficiencies.

## **Application:**

Apply DECO 20 CLEAR FINISH, without dilution, with a hand-pump sprayer or airless sprayer. For spraying application, and depending upon sprayer equipment used, it is recommended that an orifice size of 0.035 inches be used for testing to insure proper material application. Do not apply over 100 PSI. Apply DECO 20 CLEAR FINISH until saturation. Do not interrupt application process until area is completely treated.

Equipment cleans up easily with soap and water.

## **APPLY ONLY ONCE**

**WARRANTY:** DECO 20 is warranted as specified for a period of not less than one year from date of application. DECO Products, Inc. warrants its product to be good quality and will replace or refund the purchase price of any product proved defective. It is the responsibility of the buyer to determine that this product meets their needs and to apply it properly. The application of DECO 20 requires that the installer be skilled in achieving results from applying this product. Satisfactory results depend not only upon quality product, but also upon many factors beyond DECO Products, Inc.'s control. DECO Products, Inc. makes no warranty or guarantee, expressed or implied, including warranty of fitness or merchantability respecting its products. DECO Products, Inc. shall have no other liability with respect thereto. Guarantee of this product, DECO 20, when used according to directions, is limited to refund of purchase price or replacement of product, if it is proved defective. DECO Products, Inc. shall not be liable for cost of labor, direct or incidental consequential damages.

## **COVERAGE:**

On concrete approximately 375 Sq. Ft. Per gallon

On masonry block approximately 175 Sq. Ft. Per gallon

On Concrete Tiles and pavers approximately 375 Sq. Ft. Per gallon

NOTE: Coverage rates may vary due to the porosity of the substrate.

## **TECHNICAL SERVICES:**

Technical advice furnished by DECO Products, Inc., concerning any use or application of DECO 20 is reliable as current technology allows. DECO Products, Inc. makes no warranty, expressed or implied, of any use of application for which such advice is furnished. OTHER LOW VOC products for concrete, stucco, block and specialty cementitious items are available from DECO Products, Inc. Ask your representative for details.

## **Distributed by:**

**TEST DATA:** DECO 20 Clear Finish meets and/or exceeds the following ASTM tests:

ASTM D 2939 - Resistance to water solubility.

Flexibility no cracking.

ASTM D 466 - Resistance to water flow and action.

Excellent adhesion. No reemulsification.

ASTM E 96 - Water vapor transmission. - 0.04 grains/sq.ft./hour

Water vapor permeability. - 0.102 perms

ASTM C 836 - Film Thickness On Vertical Surface.

SS-W-110 C - Water Repellency On Masonry Test.

1.925% Average

ASTM C 672 - Freeze/Thaw - 20 Day Cycle

## **LIMITATIONS:**

**DO NOT GET DECO 20 CLEAR FINISH ON GLASS. DECO 20 CLEAR FINISH WILL CAUSE ETCHING OF GLASS AND CANNOT BE REMOVED.**

If DECO 20 comes in contact with glass, clean immediately with water.

**Do not let product freeze. Store indoors at temperatures above 32 degrees Fahrenheit. The temperature must be 28 degrees Fahrenheit and rising before application.**

Do not dilute DECO 20. Do not apply DECO 20 when the threat of rain is imminent. Do not apply DECO 20 on glazed tile, slate, glazed brick construction, acrylics or painted finishes. Do not use DECO 20 on colored concrete. DECO 20 will not plug holes or cracks. Cover all doors and glass openings to insure product does not come in contact with them. Use caution when applying on windy days. DECO 20 is not designed to be used as a waterproofing coating to stop moisture penetration caused by cracks or holes in the surface.

KEEP OUT OF REACH OF CHILDREN

## **INSTALLATION:**

**The use of DECO 20 on foundations in no way eliminates the use of a properly installed drainage system designed for the foundation wall or properly constructed concrete foundation wall.** DECO 20 can be applied directly to block walls after the mortar joints and parging has taken its initial set.

**NOTE: Always perform a test of DECO 20 to ensure desired results. After the sealer has dried on the substrate, apply water to see if sealer repels. If water repels, continue with the application of DECO 20 Clear Penetrating Concrete Sealer. If water absorbs into substrate and does not repel water, do not continue the application of DECO 20 Clear Penetrating Concrete Sealer. Call your local DECO representative for additional information.**



## **DECO 20 CLEAR FINISH (Penetrating Concrete Sealer)**

**DECO Products, Inc.**

**7900 E. 40th Ave.**

**Denver, Colorado 80207**

**(800) 500-3326**