

# APPLICATOR'S GUIDE

## DECO 20

### PENETRATING CLEAR SEALER

**Always perform a jobsite test prior to applying DECO 20 CLEAR SEALER to ensure desired results.**

#### LIMITATIONS:

DECO 20 CLEAR SEALER should not be applied to glass, glazed tile, painted or previously sealed materials.

Avoid drips and runs and do not over apply product. Do not interrupt application process until area is completely treated. DECO 20 CLEAR SEALER is 100% water based and cannot be reapplied to itself. If product is over applied a whitening will appear on the substrate leaving undesired results.

DECO 20 CLEAR SEALER should be applied in temperatures between 38 degrees Fahrenheit and 75 degrees Fahrenheit. It is recommended in higher temperatures and in direct sunlight to mist the substrate with water prior to applying DECO 20 CLEAR SEALER to break the surface tension. This will allow DECO 20 CLEAR SEALER to dry slower and penetrate deeper in to the substrate. This will also reduce the chance of the product whitening and uneven looking application.

DECO 20 CLEAR SEALER will not stop water from entering through cracks or holes in the material. Proper safety concerns should be followed when using any sealers. Gloves and eye protection are recommended. Always keep a SDS on hand.

**There are several different ways to apply this product depending on the budget and size of the job**

One or two gallon garden pump sprayer

Back pack pump sprayer

Four gallon pressure tank

18- 25 gallon electric tank sprayer



Light Duty



3 Pack

Light/  
Medium Duty



Large Duty



Heavy Duty

#### APPLICATION:

Inspect surface to be treated. Clean off any dirt oils or other foreign objects that could prevent DECO 20 CLEAR SEALER from penetrating the material. Apply DECO 20 CLEAR SEALER without dilution with desired equipment. Apply until saturated. Do not interrupt application process until area is completely treated. Cover all surfaces not to be treated. Do not get on glass.

Do not apply when threat of rain is imminent. Use caution on windy days to prevent over spray from contacting other surfaces.

If there is any question or concerns about application of DECO 20 CLEAR SEALER contact your representative.

DECO 20 CLEAR SEALER should be installed by a trained/ skilled applicator to ensure accurate installation. Deco Products warrants its product to be manufactured with the highest quality but cannot guaranty its performance when installed improperly.