

TECHNICAL INFORMATION

"dry as a bone"



DECO PRODUCTS, INC.

DECO 30 Brick and Stucco Sealer

Product specification

DECO 30 Penetrating Brick and Stucco Sealer is a clear formulated sealer designed for the demanding environmental requirements for waterproofing and preserving brick and stucco. DECO 30 has no solvents and extremely low VOC's (Volatile Organic Compounds). Eliminating the use and dependency of all solvent based products.



Environmentally Friendly

Totally Water- Based

Non- Hazardous


B E N E F I T S

- Reduces bacteria growth and mildew
- Harmless to humans, plants and animals
- Worker safety
- Reduces spalling of mortar joints
- Reduces efflorescence
- Non - slippery
- Reduces water transmission
- Reduces bacteria growth and mildew
- Non-toxic Non-caustic Non-flammable

Use: For approved applicators

New & existing construction: Apply DECO 30 with a hand pump sprayer directly to substrate until saturated. Do not over apply and avoid drips or runs. Do not interrupt application process. DECO 30 is a water based product and cannot be re applied. It is best to apply in morning hours or shaded areas before the substrate heats up. If applied in direct sunlight spray a light mist of water on substrate prior to application to break the surface tension. For complete application guide consult your sales rep or visit our website at decoproducts.com

Distributed by:



BUILT GREEN™

Made in the U.S.A.



S P E C I F I C A T I O N D A T A

TEST DATA:

DECO 30 meets and or exceeds the following ASTM tests:

ASTMD 2939 - Resistance to water solubility.
Flexibility no cracking.

ASTMD 466 - Resistance to water flow and action.
Excellent adhesion. No reemulsification.

ASTME 96 - Water vapor transmission. - 0.04 grains/sq.ft./hour
Water vapor permeability. - 0.102 perms

ASTM C 836 - Film thickness on vertical surface.

SS-W-110 C - Water repellency on masonry test.
1.925% average

ASTM C 672 - Freeze/Thaw - 20 Day Cycle

LIMITATIONS:

DO NOT GET DECO 30 ON GLASS. DECO 30 WILL CAUSE ETCHING OF GLASS AND CANNOT BE REMOVED. If DECO 30 comes in contact with glass, clean immediately with water.

Do not let product freeze. Store indoors at temperatures above 32 degrees Fahrenheit. Outdoor temperature must be 28 degrees Fahrenheit and rising at time of application.

Do not dilute DECO 30. Do not apply DECO 30 when the threat of rain is imminent. Do not apply DECO 30 on slate, tile, glazed tile or other glazed surfaces, including glazed brick. Do not apply DECO 30 on painted or acrylic finishes.

DECO 30 will not plug holes or cracks. DECO 30 is not designed to be used as a waterproofing coating to stop moisture penetration caused by cracks or holes in the surface.

KEEP OUT OF REACH OF CHILDREN.

INSTALLATION:

Note: Always perform a job site test to insure desired results.

Coverage: Approximately 200 to 250 square feet depending upon the porosity of the surface.

Preparation:

*Repair all structural deficiencies before applying DECO 30.

TECHNICAL SERVICES:

Technical advice furnished by DECO Products, Inc., concerning any use or application of DECO 30 is reliable as current technology allows. DECO Products, Inc. makes no warranty, expressed or implied, of any use of application for which such advise is furnished.

Protect all areas or surfaces not to be sealed, such as doors, windows and floors, prior to applying DECO 30. Use caution when applying on windy days.

Vertical Application:

Apply DECO 30, without dilution, with a hand-pump sprayer or airless sprayer. For spraying application, and depending upon sprayer equipment used, it is recommended that an orifice size of 0.015 inches or less be used for testing to insure proper material application. Apply DECO 30 until saturation while eliminating any run down. Do not interrupt application process until area is completely treated.

Horizontal Application:

For sprayer application, apply DECO 30 in mist form. Do not let DECO 30 puddle. Remove all excess material before material dries.

WARNING: Apply only once. More than one application will leave an undesirable film on the surface.

WARRANTY:

DECO 30 is warranted to perform as specified for a period of not less than three years from date of application. DECO Products, Inc. warrants it's product to be of good quality and will replace or refund the purchase price of any products proved defective. It is the responsibility of the buyer to determine that this product meets their needs and to apply it properly. The application of DECO 30 requires that the installer be skilled in achieving results from applying this product. Satisfactory results depend not only upon quality product, but also upon many factors beyond DECO Products, Inc.'s control. DECO Products, Inc. makes no warranty or guarantee, expressed or implied, including warranty of fitness or merchantability, respecting its products. DECO Products, Inc. shall have no other liability with respect thereto. Guarantee of this product, DECO 30, when used according to directions, is limited to refund of purchase price or replacement of product, if it is proved defective. DECO Products, Inc. shall not be liable for cost of labor, direct or incidental consequential damages.



DECO 30 Penetrating Brick and Stucco Sealer

DECO Products, Inc. 7900 E. 40th Ave. Denver, Colorado 80207 (800) 500-3326
